

Exterior:

- The vehicle body is white with permanent logos of PostNL Parcels Belgium, compliant with the current house style for the sake of recognizability;¹
- Length * width * height = 8.00 * 2.20 * 3.10 metres maximum (exclusive of mirrors and antenna);
- The backside is equipped with 2 doors, hinged 207 degrees, which can be fixed to the side;
- The rear part of the roof does not contain any protruding parts that would undermine or cause damage to the dock seal;
- One sliding door to the cargo hold on the passenger's or driver's side;
- The cargo hold may not be equipped with windows on the sides and/or the rear doors, so that consignments are not visible for the sake of the safety thereof;
- The vehicle is equipped with a running board that meets the following requirements:
 - Distance between the end of the bumper and the end of the running board is 25 cm minimum and 30 cm maximum;
 - The top of the running board is 45 cm maximum above the road surface in unladen condition;
 - The vehicle may be equipped with a tow bar, provided that:
 - The end of the tow bar does not extend horizontally beyond the end of the running board;
 - The top side of the tow bar is 45 cm maximum above the road surface in unladen condition.

Interior:

- Clearance height in cargo hold is at least 1.90 metres;
- Load floor height is between 530 mm and 720 mm above the road surface;
- Length of cargo hold is at least 3.70 metres;
- View from the driver's seat onto full daylight size of the rear of the vehicle;
- The driver's position is shielded in such a way that the driver cannot be hit by falling parcels if the vehicle stops suddenly for an emergency.
- The cargo hold is equipped with at least 6.0 linear metres of shelf space. If the cargo hold is ≥ 3.9 metres, at least 8.0 linear metres of shelf space must be provided. The following requirements must be taken into account:
 - On one of the two long sides of the cargo hold, the rearmost 80 cm from the end of the bumper must be free of shelves (for manoeuvring with larger parcels);
 - On the other side, the rearmost 40 cm measured from the end of the bumper must be free of shelves;
 - The shelves are at least 40 cm deep and can be folded up / down or removed;
 - The cargo hold is equipped with sufficient lighting so that the address label of a package can be read in a dark environment.

Miscellaneous:

- The turning circle over the bumper is 17.0 metres maximum;
- The car must meet at least the EURO-5 standard.

¹PostNL Parcels Belgium nv pays the first sticker of a vehicle directly to the exporter, and limits the payment of the postage label to 1 year maximum. PostNL Parcels Belgium is aware of the fact that the Contractor runs its own business. The Contractor is at all times free to affix its company's stickers on the front doors in a recognizable manner;